



PLUS POWER ISUZU Series Diesel Generator Set(1500/1800rpm)

www.pluspowergenerator.com sales1@plus-power.cn Mobile/wechat/whatsapp:+86-13959393353



		Three Phase 400V 50Hz/1500rpm				Single Phase 230V 50Hz/1500rpm			
Genset Model		ISU25-3	ISU28-3	ISU33-3	ISU45-3	ISU20-1	ISU22-1	ISU26-1	ISU35-1
Standby Power		25kVA	28kVA	33kVA	45kVA	20kVA	22kVA	26kVA	35kVA
		20kW	22kW	26kW	36kW	20kW	22kW	26kW	35kW
Prime Power		22kVA	25kVA	30kVA	40kVA	18kVA	20kVA	24kVA	32kVA
		18kW	20kW	24kW	32kW	18kW	20kW	24kW	32kW
Ampere (base on 400V) A		32.5	36.1	43.3	57.7	78.3	87.0	104.3	139.1
Engine Brand		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Engine Model		JE493DB-04	JE493DB-02	JE493ZDB-04	JE493ZLDB-02	JE493DB-04	JE493DB-02	JE493ZDB-04	JE493ZLDB-02
Cylinder *Bore*Stroke		4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm
Displacement		2.7L	2.7L	2.7L	2.7L	2.7L	2.7L	2.7L	2.7L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		184E	184F	184G	184J	184F	184G	184H	224C
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120
Fuel consumption		5.7L/h	6.5L/h	7.2L/h	8.9L/h	6.5L/h	7.6L/h	8.8L/h	11.4L/h
Capacity(L)	Fuel tank	60L	65L	75L	90L	60L	65L	75L	90L
	Coolant	7L	7L	8L	10L	7L	7L	8L	10L
	Lubrication	5.6L	5.6L	5.6L	5.6L	5.6L	5.6L	5.6L	5.6L
Open type	Demension	1450*720*1000	1450*720*1000	1450*720*1000	1600*720*1000	1450*720*1000	1450*720*1000	1450*720*1000	1700*720*1000
	Weight	470KGS	500KGS	530KGS	580KGS	470KGS	500KGS	530KGS	580KGS
Sound proof	Dimension	2100*950*1130	2200*950*1130	2100*950*1130	2200*950*1130	2100*950*1130	2200*950*1130	2100*950*1130	2300*950*1130
	Weight	700KGS	740KGS	760KGS	820KGS	700KGS	740KGS	760KGS	820KGS

		Single Phase 220V 60Hz/1800rpm				Three Phase 220V 60Hz/1800rpm			
Genset Model		ISU22-1	ISU26-1	ISU33-1	ISU44-1	ISU28-3	ISU33-3	ISU41-3	ISU55-3
Standby Power		22kVA	26kVA	33kVA	44kVA	28kVA	33kVA	41kVA	55kVA
		22kW	26kW	33kW	44kW	22kW	26kW	33kW	44kW
Prime Power		20kVA	24kVA	30kVA	40kVA	25kVA	30kVA	38kVA	50kVA
		20kW	24kW	30kW	40kW	20kW	24kW	30kW	40kW
Ampere (base on 220V) A		90.9	109.1	136.4	181.8	65.6	78.7	98.4	131.2
Engine Brand		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Engine Model		JE493DB-03	JE493DB-01	JE493ZDB-03	JE493ZLDB-01	JE493DB-03	JE493DB-01	JE493ZDB-03	JE493ZLDB-01
Cylinder *Bore*Stroke		4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm	4x93x102mm
Displacement		2.7L	2.7L	2.7L	2.7L	2.7L	2.7L	2.7L	2.7L
Alternator		Stamford copy	Stamford copy	Stamford copy	Stamford copy	Stamford copy	Stamford copy	Stamford copy	Stamford copy
Alternator Model		184F	184G	184H	224C	184E	184F	184G	184J
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120	MITSUI 6120
Fuel consumption		6.5L/h	7.6L/h	8.8L/h	11.4L/h	6.5L/h	7.6L/h	8.8L/h	11.4L/h
Capacity(L)	Fuel tank	60L	65L	75L	90L	60L	65L	75L	90L
	Coolant	7L	7L	8L	10L	7L	7L	8L	10L
	Lubrication	5.6L	5.6L	5.6L	5.6L	5.6L	5.6L	5.6L	5.6L
Open type	Demension	1450*720*1000	1450*720*1000	1450*720*1000	1700*720*1000	1450*720*1000	1450*720*1000	1450*720*1000	1600*720*1000
	Weight	470KGS	500KGS	530KGS	580KGS	470KGS	500KGS	530KGS	580KGS
Sound proof	Dimension	2100*950*1130	2100*950*1130	2100*950*1130	2300*950*1130	2100*950*1130	2200*950*1130	2100*950*1130	2200*950*1130
	Weight	700KGS	740KGS	760KGS	820KGS	700KGS	740KGS	760KGS	820KGS